

PRODUCT DESCRIPTION:

The Aquapure portable ozone generator can produce 500-4000mg/h ozone output .We uses DURAN tube with 316 Stainless Steel electrode material.

This series of ozone generator can be widely applied in varied industries for water/air sterilization and disinfection.



CONTACT INFORMATION :

AQUAPURE (SHEN ZHEN) OZONE TECHNOLOGY
R1102,University Town Business Park, Lishan Road,
Taoyuan, Nanshan, 518055 Shenzhen, China

Email: info@aquapureasia.com

Tel.: 0086-755-26605963

Cell: 0086-13715076653

Skype: mendy01271990

Website: www.aquapureozone.com

AQUAPURE ---- Portable Ozone Generator



AOT-PD-500



AOT-PA-1500



AOT-PA-2000



AOT-PA-3000



AOT-PA-4000

1. Odor Control

- Industrial odor control
- Home, Hotel
- Hospital
- Zoo

2. Agriculture Industry

- Irrigation
- Vegetables and fruit preservation

3. Water Treatment

- Drinking water
- Bottle water
- Swimming pool
- Waste water treatment

4. Health care

- SPA
- Bath

5. Meat and Food

- Food factory
- Slaughterhouse
- Poultry breeding
- Fish farm

6. Medical Device Industry

- Surgical instruments
- Dental products

7. Laundry

- Household washing
- Hotel
- Hospital
- Old people home

8. Pipe cleaning

- Beer piping
- Urinal piping

AOT-PD-500

TECHNICAL SPECIFICATION

Ozone Output	0.5 g/h at 2.5 L/min , < 20% RH at 25°C dry air
Ozone concentration	> 3.0 mg/L at 2.5 L/min air flow
Gas Flow	2.5 L/min
Material	DURAN tube and 316 S.S electrode
Output connections	OD 5.0 mm
Continuous operation	24 h/day
Cooling system	Air cooling
Ozone generating method	Corona discharge
Input voltage	110-220V AC
Operating temperature	-10 deg C — +60 deg C
Storage temperature	-20 deg C — +70 deg C
Size L x W x H	192 x 87 x 80 mm
Product packing Weight	1.55 kgs/pc
Mounting type	Wall-mounted with S.S. Bracket
Accessories	Diffuser; bracket; adapter; silicon tube, user manual



AOT-PA-1500/AOT-PA-2000

- ◆ Working Mode: Continuously work & timer work
- ◆ Corona discharge
- ◆ Air cooling , 90CFM fan(120*120*25mm)
- ◆ Voltage: 110/220VAC
- ◆ Size: 286.5x162x178mm
- ◆ Weight:6KGS
- ◆ Spare part: Power cable; silicon tube; diffuser ;user manual
- ◆ Air/water purification



Model No.	Ozone Output	Gas Flow	Generator Configuration		Power
	mg/h	L/min	Tube	Electrode	W
AOT-PA-1500	1500 (Dry air)	7	Quartz Tube	316Stainless Steel;	60
AOT-PA-2000	2000 (Dry air)	10	Quartz Tube	316Stainless Steel;	65



AOT-PA-3000/AOT-PA-4000

- ◆ Working Mode: Continuously work & timer work
- ◆ Corona discharge
- ◆ Air cooling , 110CFM fan (120*120*38mm)
- ◆ Voltage: 110/220VAC
- ◆ Size: 382x203x234mm
- ◆ Weight:8KGS
- ◆ Spare part: Power cable; silicon tube; diffuser ;user manual
- ◆ Air/water purification

Model No.	Ozone Output	Gas Flow	Generator Configuration		Power
	mg/h	L/min	Tube	Electrode	W
AOT-PA-3000	3000 (Dry air)	15	Quartz Tube	316Stainless Steel;	90
AOT-PA-4000	4000 (Dry air)	22	Quartz Tube	316Stainless Steel;	100

